




# S SERIES SPECIFICATIONS



**STENNER PUMPS®**

## S30 Models





SHIPPING WEIGHT 9 lbs (3.7 kg)

## S40 Models



CONFORMS TO ANSI/NSF STD. 50 Equipment for swimming pools, spas, hot tubs and other recreational water facilities.



SHIPPING WEIGHT 9 lbs (3.7 kg)

### FEATURES

- Digital keypad with OLED display
- Tube leak detector, Tube change timer, Password protection
- Multiple operational modes
- Totally enclosed housing, NEMA 4X
- Brushless DC motor with ball bearing support
- Switch mode power supply
- 3-point roller design assists in anti-siphon protection
- Self-priming against maximum working pressure, foot valve not required
- Pump does not lose prime or vapor lock
- Pumps off-gassing solutions and can run dry
- Output volume is not affected by back pressure
- Tube replacement without tools
- Models (Santoprene® tube) tested by IAPMO to conform to ANSI/NSF STD 61 & 372
- S30 models tested by Intertek to conform to CE IP65
- S40 models tested by Intertek to conform to NSF 50 (with 5X tube & ball check valve with FKM seat & O-ring, tantalum spring, ceramic ball)

### SPECIFICATION

- Flow Rate Output Control** Varies per control mode; digital keypad
- Reproducibility** ±2%
- Maximum Working Pressure** 25 psi (1.7 bar), 100 psi (6.9 bar)
- Maximum Operating Temperature** 104°F (40°C)
- Maximum Altitude** 6562 ft. (2000 m)
- Maximum Suction Lift** 25 ft. (7.6 m) vertical lift, based on water
- Motor Type** Brushless DC motor
- Shaft rpm** (average maximum) 45
- Duty Cycle** Continuous
- Maximum Viscosity** 1500 Centipoise
- Motor Voltage (Amp Draw)**  
120V 60Hz 1PH (0.6), 230V 50Hz 1PH (0.3)
- Hall Effect Max. Input Frequency** 100 KHz
- Pulse Duration Required** 10 milliseconds  
Minimum duration required for pump to read signal.
- Power Cord Type** 120V 60Hz SJTOWA, 230V 50Hz H05RN-F
- Power Cord Plug End** 120V 60Hz 5-15P, 230V 50Hz CEE7/7
- Power Cord Length** 6 ft (1.8 m)
- Classification** Indoor/Outdoor

# S SERIES SPECIFICATIONS

## S SERIES S30 Models

### MATERIALS OF CONSTRUCTION

**All Housings** Polycarbonate

**Pump Tube**

Santoprene® (FDA approved), or Versilon®

**Check Valve Duckbill**

Santoprene® (FDA approved), or Pellethane®

**Pump Head Rollers** Polyethylene

**Roller Bushings** Oil impregnated bronze

**Suction/Discharge Tubing, Ferrules 1/4" & 6 mm**

Polyethylene (FDA approved)

**Tube Fittings, Injection Fittings**

PVC or Polypropylene (both NSF listed)

**Connecting Nuts**

PVC or Polypropylene (both NSF listed)

**3/8" Adapter**

PVC or Polypropylene (both NSF listed)

**Suction Line Strainer and Cap**

PVC or Polypropylene (both NSF listed); ceramic weight

**All Fasteners** Stainless steel

**Pump Head Latches** Polypropylene

**Leak Detect Components** Hastelloy\*\*

NOTE: Refer to the chemical guide for material compatibility.

### ACCESSORIES

3 Connecting Nuts 1/4" or 3/8"

3 Ferrules 1/4" or 6 mm *Europe*

1 Injection fitting 25 psi (1.7 bar) max. or Injection check valve 100 psi (6.9 bar) max.

1 Weighted suction line strainer 1/4", 3/8" or 6 mm *Europe*

1 20' Roll of suction/discharge tubing 1/4" or 3/8", white, UV black or 6 mm white *Europe*

1 Additional pump tube

2 Additional latches

1 Mounting bracket

1 Quick Start Guide

Download complete S Series Manual [www.stenner.com](http://www.stenner.com)

### 25 psi (1.7 bar) maximum FLOW RATE OUTPUTS

Model	Item Number Prefix	Pump Tube	Turndown Ratio	Gallons per Day	Gallons per Hour	Ounces per Hour	Ounces per Minute	Liters per Day	Liters per Hour	Milliliters per Hour	Milliliters per Minute
S3003	<b>S3003</b>	3	100:1	0.40-40.0	0.017-1.67	2.13-213.0	0.036-3.56	1.51-151.0	0.063-6.31	63.09-6309.0	1.05-105.0
S3004	<b>S3004</b>	4	100:1	0.60-60.0	0.025-2.50	3.20-320.0	0.053-5.33	2.27-227.0	0.095-9.46	94.64-9464.0	1.58-158.0
S3005	<b>S3005</b>	5	100:1	0.85-85.0	0.035-3.54	4.53-453.0	0.076-7.56	3.22-322.0	0.134-13.41	134.07-13,407.0	2.23-223.0

Approximate Outputs @ 50/60Hz

### 100 psi (6.9 bar) maximum FLOW RATE OUTPUTS

Model	Item Number Prefix	Pump Tube	Turndown Ratio	Gallons per Day	Gallons per Hour	Ounces per Hour	Ounces per Minute	Liters per Day	Liters per Hour	Milliliters per Hour	Milliliters per Minute
S3001	<b>S3001</b>	1	100:1	0.05-5.0	0.002-0.21	0.27-27.0	0.004-0.44	0.19-19.0	0.008-0.79	7.89-789.0	0.13-13.0
S3002	<b>S3002</b>	2	100:1	0.17-17.0	0.007-0.71	0.91-91.0	0.015-1.51	0.64-64.0	0.027-2.68	26.81-2681.0	0.45-45.0
S3007	<b>S3007</b>	7	100:1	0.40-40.0	0.017-1.67	2.13-213.0	0.036-3.56	1.51-151.0	0.063-6.31	63.09-6309.0	1.05-105.0

Approximate Outputs @ 50/60Hz

## S SERIES S40 Models

### MATERIALS OF CONSTRUCTION

**All Housings** Polycarbonate

**Pump Tube** Santoprene®, FDA approved

**Ball Check Valve Components**

Ceramic ball (FDA approved); Tantalum spring; FKM seat & O-ring

OR

Ceramic ball (FDA approved); Stainless steel spring; EPDM seat; Santoprene® O-ring

**Pump Head Rollers** Polyethylene

**Roller Bushings** Oil impregnated bronze

**Suction/Discharge Tubing**

Polyethylene (FDA approved)

**Tube Fittings, Injection Fittings**

PVC or Polypropylene (both NSF listed)

**Connecting Nuts**

PVC or Polypropylene (both NSF listed)

**Suction Line Strainer and Cap**

PVC or Polypropylene (both NSF listed); ceramic weight

**All Fasteners** Stainless steel

**Pump Head Latches** Stainless steel

**Leak Detect Components** Hastelloy\*\*

NOTE: Refer to the chemical guide for material compatibility.

### ACCESSORIES

3 Connecting nuts 3/8"

1 Injection ball check valve

1 Weighted suction line strainer 3/8"

1 20' Roll of suction/discharge tubing 3/8", white or UV black

1 Additional pump tube

1 Mounting bracket

1 Quick Start Guide

Download complete S Series Manual [www.stenner.com](http://www.stenner.com)

### 25 psi (1.7 bar) maximum FLOW RATE OUTPUTS

Model	Item Number Prefix	Pump Tube	Turndown Ratio	Gallons per Day	Gallons per Hour	Ounces per Hour	Ounces per Minute	Liters per Day	Liters per Hour	Milliliters per Hour	Milliliters per Minute
S405X	<b>S405X</b>	5X	100:1	1.5-150.0	0.06-6.25	8.0-800.0	0.13-13.33	5.7-567.0	0.24-23.66	236.59-23,659.0	3.94-394.0

Approximate Outputs @ 50/60Hz

### 100 psi (6.9 bar) maximum FLOW RATE OUTPUTS

Model	Item Number Prefix	Pump Tube	Turndown Ratio	Gallons per Day	Gallons per Hour	Ounces per Hour	Ounces per Minute	Liters per Day	Liters per Hour	Milliliters per Hour	Milliliters per Minute
S407X	<b>S407X</b>	7X	100:1	0.60 - 60.0	0.03-2.50	3.2-320.0	0.053-5.34	2.3-227.0	0.09-9.46	94.64-9464.0	1.58-158.0

Approximate Outputs @ 50/60Hz

\* Santoprene® is a registered trademark of Exxon Mobil Corporation.\*\* Versilon® is a registered trademark of Saint-Gobain Performance Plastics. † Pellethane® is a registered trademark of Lubrizol Advanced Materials, Inc.

\*\* Hastelloy® is a registered trademark of Haynes International, Inc.

**NOTICE:** The information within this chart is solely intended for use as a guide. The output data is an approximation based on pumping water under a controlled testing environment. Many variables can affect the output of the pump. Stenner Pump Company recommends that all metering pumps undergo field calibration by means of analytical testing to confirm their outputs. The information contained in this flyer is not intended for specific application purposes. Stenner Pump Company reserves the right to make changes to prices, products, and specifications at any time without prior notice.