PAR38-26-940-40D-ND

Project:	Туре:	Prepared By:	Date:
		HIGH OUTPUT PAR EXCEPTIONAL 900 UNIVERSAL voltage DAMP RATED - Sui SHATTERPROOF - applications ENCLOSED FIXTUR fixtures	
LISTED	UPC: 019813834368	Energy y La	
Technical Spec	cifications		

Technical S	Specifications
-------------	----------------

Product Type	HID	Electrical Characteri	stics	
Bulb Shape Wattage Typical Lumen Output Efficacy Color Temperature	PAR38 26W 2400 92 lm/W 4000K Cool White	Input Voltage Power Factor Operating Frequency Input Current @ 120V	120-277V 0.9 60 Hz 225mA	
CRI R9 Value Base Type	90 >50 E26	Input Current @ 277V Flicker Listings	105mA <30%	
L70 Lifespan	25,000 hours	UL Listed	Yes	
Operating Temperature Dimmable	-25°C - 40°C No	ENERGY STAR V2.0	This product is ENERGY STAR® Version 2.0 Certified	
Beam Angle	40°	Energy Star Model Number P10002		
Warranty For Use in Emergency Fixtures For Use Outdoors in Open Fixtures	4-Year, No-Compromise Warranty No No	CEC Status	Lawful for sale in California	

RAB

PAR38-26-940-40D-ND

Case and Pallet Dimensions

	QTY	LENGTH	WIDTH	HEIGHT
CASE	6	15.4	10.4	6.5
PALLET	480	50.1	37.6	47.6

Dimension



