



**Corrugated Stainless Steel Flexible
 Water Heater/ Softener Connectors
 Specification Sheet**

SPECIFICATION:

Furnish and install Ultra Flexible Corrugated Stainless Steel Water Heater/Softener Connector

DESIGN FEATURES: Mega-flow SUPER Water-flex™

- 304 Series Stainless Steel
- True .72" ID
- Flows approx 135% more than braided type
- Maintains optimum flow – no restriction
- Kink and Crimp Free
- Chrome plated brass nuts
- Extremely Flexible
- Will not corrode or rust
- No Dielectric union required
- Highest Quality EPDM washer
- Resists work hardening
- Working pressure 200 psi
- Burst pressure approx 1850 psi
- 100% Leak Tested
- No Sweat Installation
- Lifetime Warrantee
- Temperature rating 40 – 250 degrees F
- Bright annealed

COMPLIANCES/LISTINGS:

- * ICC-ES PMG
- * ICC Listed, Tested & Certified
- * UPC, IPC, IMC, IRC (USA)
- * Low Lead Compliant California Health & Safety Code 116875
- * ASME A112.18.6/CSA B125.6-2009 Compliant
- * NSF-61 (ICC-ES PMG Certified to ANSI/NSF section 9)
- * State of Wisconsin, Commonwealth of Massachusetts

<u>Model #</u>	<u>Description</u>	<u>Length</u>
SWC34006	3/4" FIP x 3/4" FIP	6"
SWC34012	3/4" FIP x 3/4" FIP	12"
SWC34015	3/4" FIP x 3/4" FIP	15"
SWC34018	3/4" FIP x 3/4" FIP	18"
SWC34024	3/4" FIP x 3/4" FIP	24"



<u>Product Submittal</u>	
Job Name:	_____
Date:	_____
Model#	Quantity: _____

Architect/Contractor: _____	