



## Liquidtight Flexible Non-Metallic Conduit & Fittings

T&B Catalog Number:

15011-050

UPC Number:

03448123348

Status:

Active

Description:

2 inch gray liquidtight flexible non-metallic conduit, 50 Foot coil.

### Features

Non-conductive and non-corrosive.

Lightweight for easy handling, transportation and installation.

Crush, abrasion and strain resistant.

Provides superior wire protection

Smooth interior ideal for pulling cable, no jagged edges.

Maintains internal I.D. even in tight radius bends.

Resistant to oil, acid, ozone, and alkaline.

UL listed for outdoor use and sunlight resistant.

UL listed for use as indicated in Article 356.2 of the NEC and Section 12-1300 of the Canadian Electrical Code, Part 1.

Suitable for use at conduit temperatures of 80 degree C dry, 60 degree C wet and 60 degree C oil resistant as required by Section 15-6 of ANSI/NFPA 79 and UL 1660.

Sequentially market footage

### Application

Control and Motor

Air conditioning and heating

Computer power distribution

Machine Tools

Console wiring

Transformer connections

Outdoor lighting

### General

Material Non-Metallic

Color Gray

### Dimension Information

Size (inches) 2

Average O.D. (inches) 2.357

Average I.D. (inches) 2.025

Nominal Size (inches) 2

Coil Length (feet) 50

### Packaging

T&B Order Multiple 50

Package in Units 50

T&B Sold in UOM Feet

T&B Weight Per UOM 64.44 lbs. per 100

### Application Support

Product Overview-Carflex Liquidtight Flex-Available on Website  
ible Tubing

## Notes

Available in black and gray.

Customer cut lengths available.

## Certifications

RoHS Compliance

Yes

## Certifications



File Nbr:

E 79553

### For further technical assistance, please contact us...

Thomas & Betts - USA  
8155 T&B Blvd.  
Memphis, TN 38125  
www.tnb.com

T&B Technical Support  
MS 3B-50  
8155 T&B Blvd.  
Memphis, TN 38125

Hours: 7AM - 6PM CDT  
Monday-Friday  
Phone: (888) 862-3289  
Fax: (901) 252-1321  
Email:techsupport@tnb.com