

DX-treme C-Series

Revised 8/29/13

C A 24 A3 G -145 L -001

①

②

③

④

⑤

⑥

⑦

⑧

⑧ Option Code

⑦ **Refrigerant and plumbing connections**

L = left-hand plumbing and refrigerant connections

R = right-hand plumbing and refrigerant connections

T = refrigerant out the top, plumbing out opposite sides

⑥ CA, CM Series: Drain pan width code
CB, CC, CE, CP, CQ, CR, CS Series: Furnace width code
CH Series: cabinet width code

⑤ **Metering device**

4 = non-bleed A/C or H/P R410 TXV

6 = 20% bleed A/C or H/P R410 TXV

B = 20% bleed A/C or H/P R22 TXV

F = R-22 Flo-rater

G = R-410A Flo-rater

X = non-bleed A/C or H/P R22 TXV

④ **Coil descriptor code** (face area, rows, fpi)

③ **Nominal tonnage (MBTUH)**

② **Configuration**

A = uncased up/down

B = cased dedicated horizontal LaborSaver

C = cased up/down

E = cased multi-position VersaCoil

H = cased dedicated horizontal slab coil

M = manufactured home coil

P = cased dedicated horizontal with attached plenum

Q = cased dedicated horizontal with attached plenum and built-in auxiliary drain

R = cased dedicated horizontal with attached plenum and built-in auxiliary drain, 2nd generation

S = cased dedicated horizontal LaborSaver, 2nd generation

① **Series**

C = C Series (DX-treme)