

ProPEX lead-free (LF) brass elbows (PEX and PEX)

| Project information | |
|---------------------------------|-----------------|
| Job name : | Location: |
| Engineer: | Date submitted: |
| Contractor: | Submitted by: |
| Manufacturer's representative : | Approved by : |

Technical data

Material LF Brass


Temp/pressure ratings 73 °F (23 °C) at 160 psi (11 bar) 180 °F (82 °C) at 100 psi (6.9 bar)

200 °F (93 °C) at 80 psi (5.5 bar)

Prop 65 label required? Yes

Product information and application use

Uponor ProPEX® lead-free (LF) brass elbows are available for use in hot and cold domestic potable water systems, hydronic heating and cooling systems, and AquaSAFE™ residential fire safety systems. Each end features the ProPEX fitting for connections to Wirsbo hePEX™ or Uponor AquaPEX® pipe. This product is safe for direct burial in soil.



| Part n | ame | Part no. | A [inch] | B [inch] | C [inch] | D [inch] | E [inch] | F [inch] | G [inch] | Weight per UOM [lbs/UOM] | End Type 1 | End Type 2 |
|-----------------|------------------------------------|-----------|-------------|-------------|-------------|-------------|-------------|-------------|-------------|--------------------------------|----------------|----------------|
| ProPE 1/2" P | X LF Brass Elbow, 1/2" PEX x EX | LF4710500 | 0.709 | 0.437 | 0.469 | 1.455 | 1.487 | 0.87 | 0.3 | 0.2 | ProPEX 1/2" | ProPEX 1/2" |
| ProPE 3/4" P | X LF Brass Elbow, 3/4" PEX x EX | LF4710750 | 0.945 | 0.695 | 0.4 | 2.078 | 1.782 | 1.2 | 0.406 | 0.2 | ProPEX 3/4" | ProPEX 3/4" |
| ProPE PEX | X LF Brass Elbow, 1" PEX x 1" | LF4711000 | 1.181 | 0.879 | 0.55 | 2.615 | 2.287 | 1.46 | 0.55 | 0.3 | ProPEX 1" | ProPEX 1" |

nstallation Related applications

ProPEX expansion tools and ProPEX rings (sold separately) are required for connecting the PEX pipe. Refer to the Uponor piping systems installation guide, Radiant floor heating installation handbook or the AquaSAFE residential fire sprinkler installation guide for additional information.

PEX-a Plumbing Systems

Uponor Residential Fire Safety Systems

Radiant Heating and Cooling Systems

Permafrost Protection Systems

Turf Conditioning Systems

| C | Codes | Standards | Listings |
|---|--|---|---|
| L | UPC IBC IRC IPC NPC of Canada UMC NSPC IMC | NSF-372 ASTM F877 ASTM F1960 CSA B137.5 UL 1821 NSF- 61 NSF-14 | IAPMO-ES cNSFus-pw-fs-G ICC-ES-PMG U.P.Code |

| Footnotes | Contact information | | | | |
|-----------|------------------------|-------------------------|--|--|--|
| | Uponor Inc. | Uponor Ltd. | | | |
| | 5925 148th Street West | 6510 Kennedy Road | | | |
| • | Apple Valley, MN 55124 | Mississauga, ON L5T 2X4 | | | |
| | T 800.321.4739 | T 888.594.7726 | | | |
| | F 952.891.2008 | F 800.636.9517 | | | |