

## **PRODUCT DATA SHEET**

3-36® Multi-Purpose Lubricant & Corrosion Inhibitor, 5 Wt Oz

No. 03004 | Item# 1003253 | Case# 1003252

Product Description A versatile petroleum based compound that forms a clear,

thin film that lubricates and protects against wear and corrosion. Multi-purpose product lubricates, protects,

displaces moisture, and cleans.

Applications Tubing, castings, gears, weld rod, wire, fixtures, dies, jigs,

shim stock, chucks, drill rod, heat treated parts, machined surfaces, finished welds, aluminum extrusions, air

actuated tools, conveyors, frozen joints, locks, hoists, etc.

Unit Package Description 6 Ounce Aerosol

Brand CRC

Generic Description 1 Multi-Purpose Precision Lubricant & Corrosion Inhibitor

Net Fill 5 Wt Oz

UPC Code 078254030043

Unit Dimensions 5.5H x 2W x 2D in

Units Per Case 12

Case Dimensions 5.75H x 6.75W x 8.75D in

Cases Per Pallet 280
Case Weight 5 lbs

1 2 of 5 Code 30078254030044

Appearance Clear Blue-Green Liquid

Base Type Petroleum

Flash point (F) 192°F Flash point (C) 89°C

Flammability Class - CPSC Flammable

Spec Gravity Concentrate 0.827

Plastic Safe No

Film Type Non-Drying

Film Thickness 0.025 to 0.075 Mils

Evaporation Rate Slow

Last revised: 11/28/2017

Page 1 of 2



**lulti-Purpose Lubricant** 

& Corrosion Inhibitor

Slops Squeaks & Squeals
Subricales & Protects All Metals
Sisplaces Moisture &

etas de uso y advertencias de dad del producto en Español.

> SKIN REACTION. S UNDER PRESSURE

AWAY FROM CHILDREN.

Frees Rusted Parts

Stops Corrosion

DANGER: FLAMMABLE. HARMFUL OR FATAL IF SWALLOWED. MAY CAUSE AN

CRC Industries is a worldwide leader in the production of specialty chemicals for maintenance and repair professionals serving industrial, electrical, aviation, automotive and marine markets. CRC is ISO 9001:2008 certified

and adheres to the strictest guidelines for quality in all facets of research, development and production.



## **PRODUCT DATA SHEET**



38,800 Volts Dielectric Strength Working Temp (F) -50 to 250°F Working Temp (C) -45.6 to 121.1°C Propellant Carbon Dioxide

**NSF Category Code** H2

**NSF Number** 017411 Federal Specification V-V-P-216, O-W-1284

Number

Aerosol Flammability Level Ш

**DOT Proper Shipping Name** Aerosols, Flammable, Limited Quantity

0

0

0

VOC % (Consumer Product def)

VOC g/L (Consumer

Product def) VOC lbs/gal (Consumer

**VOC Category** 

Prod def)

Multi-Purpose Lubricant

Removal (How To) Remove with petroleum products, mineral spirits, or

contact cleaner.

Last revised: 11/28/2017

Page 2 of 2



CRC Industries is a worldwide leader in the production of specialty chemicals for maintenance and repair professionals serving industrial, electrical, aviation, automotive and marine markets. CRC is ISO 9001:2008 certified

and adheres to the strictest guidelines for quality in all facets of research, development and production.