


Submittal Sheets

Four Hole Corner Joiner Plate Wt. 75#/C



Specifications

GENERAL

H-STRUT General Fittings are designed to fit with all H-STRUT 15/8" wide channels. All H-STRUT fittings are manufactured from 1/4" thick carbon steel, 15/8" wide, all holes are \(^9/16\)" diameter, spaced 1\(^7/8\)" on center and \(^{13}/16\)" from the end.

MATERIAL

H-STRUT fittings are manufactured from the following

- ☐ Hot Rolled Steel Sheet ASTM A-1011 or Cold Rolled Steel Sheet ASTM A-1008 ☐ Stainless Steel-Type 304/316L...ASTM A-240
- ☐ Aluminum Fitting.....ASTM B-221

FINISHES

- ☐ Electro Galvanized ASTM B-633 ☐ Hot Dipped Galvanized. ASTM A-123
- ☐ Zinc Trivalent Chromium. ASTM B-633-85

(See technical section for additional information)

H-STRUT fittings are available in the following finishes:

- ☐ Powder Coated Supr-Green....ASTM B-117
- □ PVC Coating Available Upon Request

ORDERING

Please specify catalog number and finish.

Holes are $\frac{9}{16}$ " diameter, spaced $\frac{17}{8}$ " on center and $\frac{13}{16}$ " from end.

Project Information			
Project:			Notes:
Address:			
Contractor:			
Engineer:		Date:	
Approval Approval			
☐ Approved	Signature:		Remarks:
☐ Approved as Noted			
☐ Not Approved			