

PVC Coated Mogul Fittings - BC

Calbond mogul style conduit bodies are used where an extra large wiring space is required. They are available in all styles. Sealing mating between cover and fittings are provided. Covers are sold separately.

Features:

- Exterior PVC coating thickness is a minimum 0.040"
- Interior Urethane coating thickness is a minimum 0.002"
- Sizes available are 1" to 4"
- · Sealing sleeves on all hubs

Standards:

• UL Listed Standard 514B

• CSA Standard: C22.2 No. 18



BC								
Item Number	Trade Size	Weight Per 100 (lbs)	A	В	С	D	Е	Aluminum Item Number
PV1000BC3	1"	3.2	7.31	1.92	2.27	1.88	6	PA1000BC3SA
PV1200BC4	1-1/4"	4.0	8.50	2.35	2.27	1.88	6	PA1200BC4SA
PV1500BC5	1-1/2"	5.9	10.38	2.60	3.08	2.63	10	PA1500BC5SA
PV2000BC6	2"	7.8	12.25	3.17	3.08	2.63	10	PA2000BC6SA
PV2500BC7	2-1/2"	12.5	15.63	3.67	4.33	3.81	15	PA2500BC7SA
PV3000BC8	3"	17.0	15.63	4.42	4.33	3.81	15	PA3000BC8SA
PV3500BC9	3-1/2"	25.0	18.75	4.92	5.33	4.75	20	PA3500BC9SA
PV4000BC10	4"	28.0	18.75	5.42	5.33	4.75	20	PA4000BC10SA