













Outdoor Lighting Quick Reference Guide



AREA LIGHTING

		Value Proposition in 30 Seconds	Lumen Packages	CCT & CRI	Voltage	Optional								
						Motion Sensor	Emergency Battery	nLIGHT AIR	CS					
RADEAN™	 RAD1 LED	Architecturally stunning by day, visually comfortable illumination by night, the Radean family is ideal for pedestrian spaces.	P1 - 3,000 lumens, 25W P2 - 5,000 lumens, 38W P3 - 7,000 lumens, 54W P4 - 11,000 lumens, 86W P5 - 16,000 lumens, 122W	3000K / 80 CRI 4000K / 80 CRI	MVOLT (120 – 277V)	High / Low Motion Sensor	-	Yes (no motion sensor)	-					
	 RADPT LED		P1 - 3,000 lumens, 25W P2 - 5,000 lumens, 38W P3 - 7,000 lumens, 54W P4 - 10,000 lumens, 86W P5 - 15,000 lumens, 123W							5000K / 80 CRI	HVOLT (347 – 480V)			
D-Series LED Area Lighting	 DSX0 LED 20-LED		The D-Series family of LED area luminaires is the ideal solution for new construction where maximum poles spacing, low power density and superior uniformity are desired. With over 15 optics, including special back-light control optics, the D-Series ensures outstanding application efficiency.	P1 - 4,000 lumens, 38W P2 - 5,000 lumens, 49W P3 - 7,000 lumens, 71W P4 - 10,000 lumens, 92W	3000K / 70 CRI 4000K / 70 CRI					MVOLT (120 – 277V)	High / Low Motion Sensor with Integral Photocell	-	Yes	-
	 DSX0 LED 40-LED			P5 - 10,000 lumens, 89W P6 - 15,000 lumens, 134W P7 - 17,000 lumens, 166W										
	 DSX1 LED 60-LED			P8 - 23,000 lumens, 207W P9 - 26,000 lumens, 241W	Phosphor-Convert Amber					XVOLT (277 – 480V)				
	 DSX2 LED 80-LED			P1 - 18,000 lumens, 140W P2 - 23,000 lumens, 185W P3 - 27,000 lumens, 217W P4 - 32,000 lumens, 270W P5 - 36,000 lumens, 321W	Limited Wavelength Amber									
	 DSX2 LED 100-LED			P6 - 39,000 lumens, 343W P7 - 44,000 lumens, 398W P8 - 47,000 lumens, 448W										







AREA LIGHTING

		Value Proposition in 30 Seconds	Lumen Packages	CCT & CRI	Voltage	Optional			
						Motion Sensor	Emergency Battery	nLIGHT AIR	CS
RSX LED Area Lighting	 RSX1 LED	The RSX LED area luminaires are a complete solution for both renovation and new construction applications where value, an extensive range of options and industry-leading delivery are required.	P1 - 7,000 lumens, 51W	3000K / 70 CRI 4000K / 70 CRI 5000K / 70 CRI	MVOLT (120 – 277V) HVOLT (347 – 480V) XVOLT (277 – 480V)	High / Low Motion Sensor with Integral Photocell (using nLight AIR)	-	Yes	-
			P2 - 10,000 lumens, 72W						
			P3 - 14,000 lumens, 109W						
			P4 - 16,000 lumens, 133W						
	 RSX2 LED		P1- 11,000 lumens, 71W						
			P2 - 17,000 lumens, 111W						
			P3 - 22,000 lumens, 147W						
			P4 - 25,000 lumens, 187W						
			P5 - 29,000 lumens, 210W						
	 RSX3 LED		P1 - 27,000 lumens, 194W						
			P2 - 30,000 lumens, 222W						
			P3 - 35,000 lumens, 266W						
			P4 - 40,000 lumens, 312W						
	 RSX4 LED		P1 - 40,000 lumens, 275W						
			P2 - 45,000 lumens, 320W						
			P3 - 50,000 lumens, 369W						
	P4 - 55,000 lumens, 431W								
	P5 - 62,000 lumens, 483W								
	P6 - 69,000 lumens, 546W								
ESX LED	 ESX1 LED	The ESX LED area luminaire provides the best value in area lighting. Eight configurations are in stock at all Acuity distribution centers.	P2 - 14,000 / 8,000 lumens, 98W / 50W	4000K / 70 CRI	MVOLT (120 – 277V)	-	-	-	Yes
			P4 - 25,000 / 21,000 lumens, 190W / 146W	5000K / 70 CRI	HVOLT (347 – 480V)				








WALL-MOUNTED LIGHTING

		Value Proposition in 30 Seconds	Lumen Packages	CCT & CRI	Voltage	Optional						
						Motion Sensor	Emergency Battery	nLIGHT AIR	CS			
WDGE LED Wall-Mount	WDGE1 LED	The WDGE family of LED wall-mounted luminaires uses four sizes, two optical technologies and one common shape to create a true site-wide solution with all the egress lighting and controls options specifiers demand.	P1 - 1200 lumens, 10W P2 - 2000 lumens, 15W	2700K / 80 CRI 3000K / 80 CRI	MVOLT (120 – 277V) 347V	-	4W / 0C	-				
	WDGE2 LED		P1 - 1200 lumens, 10W P2 - 2000 lumens, 15W P3 - 3,000 lumens, 23W P4 - 4,500 lumens, 35W P5 - 6,000 lumens, 48W	3500K / 80 CRI 4000K / 80 CRI 5000K / 80 CRI (90 CRI also available)	MVOLT (120 – 277V) 347V 480V	High / Low Motion Sensor with Integral Photocell	4W / 0C 10W / 5C 18W / -20C	Yes				
	WDGE3 LED		P1 - 7,500 lumens, 52W P2 - 8,500 lumens, 59W P3 - 10,000 lumens, 71W P4 - 12,000 lumens, 88W	3000K / 80 CRI 4000K / 80 CRI 5000K / 80 CRI (70 CRI also available)			15W / 5C 18W / -20C	Yes		-		
	WDGE4 LED		P1 - 12,000 lumens, 77W P2 - 16,000 lumens, 106W P3 - 18,000 lumens, 123W P4 - 20,000 lumens, 140W P5 - 22,000 lumens, 156W P6 - 25,000 lumens, 185W	-	-	-	Yes					
ARC LED Wall-Mount	ARC1 LED		Upgrade your expectations when you upgrade your wall-mounted lighting. The ARC LED family makes architectural styling and visually comfortable illumination affordable, meeting the needs of both new construction and renovation projects.	P1 - 1,500 lumens, 11W P2 - 2,000 lumens, 17W P3 - 3,000 lumens, 25W	3000K / 80 CRI 4000K / 80 CRI 5000K / 80 CRI	MVOLT (120 – 277V) 347V	-	4W / 0C		-	-	
	ARC2 LED			P1 - 1,500 lumens, 11W P2 - 2,000 lumens, 16W P3 - 3,000 lumens, 24W P4 - 4,000 lumens, 30W P5 - 6,500 lumens, 51W				4W / 0C 8W / -20C				
WPX LED Wall-Mount	WPX1 LED			The WPX family provides the best value in full cut-off wall-mounted lighting. Low initial cost, high energy savings, great styling and emergency egress lighting options make it the distributor and contractor's choice for their everyday lighting needs.	P1 - 1,550 lumens, 11W P2 - 2,900 lumens, 24W	3000K / 70 CRI 4000K / 70 CRI 5000K / 70 CRI	MVOLT (120 – 277V) 347V	-		4W / 0C	-	Yes
	WPX2 LED				6,000 lumens, 47W					14W / -20C		Yes
	WPX3 LED				9,200 lumens, 69W					-		-








WALL-MOUNTED LIGHTING

		Value Proposition in 30 Seconds	Lumen Packages	CCT & CRI	Voltage	Optional			CS				
						Motion Sensor	Emergency Battery	nLIGHT AIR					
TWX LED (Glass) Wall-Mount	 TWX1 LED	Not your father's glass wall pack! The TWX LED family of glass wall packs provide traditional styling with superior illumination and fast pay-back. The Adjustable Lumen Output (ALO) feature makes the TWX LED the ideal distributor stock product, allowing one product to replace a wide range of HID wall packs.	P1 - 1,600 lumens, 11W P2 - 2,950 lumens, 22W ALO - 600 – 2,950 lumens, 4 – 22W	3000K / 80 CRI 4000K / 80 CRI 5000K / 80 CRI	MVOLT (120 – 277V)	-	-	-	Yes				
	 TWX2 LED		P1 - 3,250 lumens, 23W P2 - 4,400 lumens, 32W P3 - 5,250 lumens, 39W P4 - 6,850 lumens, 54W ALO - 1,450 – 6,850 lumens, 9 – 54W		MVOLT (120 – 277V) 347V 480V				Yes				
	 TWX3 LED		P1 - 8,800 lumens, 65W P2 - 10,650 lumens, 79W P3 - 12,900 lumens, 97W P4 - 13,850 lumens, 108W ALO - 2,900 – 13,850 lumens, 18 – 108W		MVOLT (120 – 277V) 347V				Yes				
TWPX LED (Polycarbonate) Wall-Mount	 TWPX1 LED		The vandal-resistant TWPX LED features a polycarbonate lens, making it ideal for low mounting height applications in high-traffic areas.	P1 - 1,450 lumens, 11W P2 - 2,700 lumens, 22W ALO - 550 – 2,700 lumens, 4 – 22W	3000K / 80 CRI 4000K / 80 CRI 5000K / 80 CRI				MVOLT (120 – 277V)	-	-	-	-
	 TWPX2 LED			P1 - 3,150 lumens, 23W P2 - 4,250 lumens, 32W P3 - 5,050 lumens, 39W P4 - 6,600 lumens, 54W ALO - 1,400 – 6,600 lumens, 9 – 54W					MVOLT (120 – 277V) 347V 480V				-
	 TWPX3 LED			P1 - 8,400 lumens, 65W P2 - 10,150 lumens, 79W P3 - 12,300 lumens, 97W P4 - 13,200 lumens, 108W ALO - 2,750 – 13,200 lumens, 18 – 108W					MVOLT (120 – 277V) 347V				Yes

FLOODLIGHTING






		Value Proposition in 30 Seconds	Lumen Packages	CCT & CRI	Voltage	Optional						
						Motion Sensor	Emergency Battery	nLIGHT AIR	CS			
D-Series LED Floodlighting	 DSXF1 LED	The D-Series LED flood family is designed to meet the floodlight needs of specifiers while keeping the project on budget. With three sizes, seven different optics, a wide selection of mounting options and accessories, and lumen packages from 2,700 to 26,000, the D-Series LED flood family can be configured to meet the needs of any floodlighting application.	P1 - 2,700 lumens, 21W P2 - 5,000 lumens, 42W	3000K / 70 CRI 4000K / 70 CRI 5000K / 70 CRI	MVOLT (120 – 277V) 347V	-	-	-	-			
	 DSXF2 LED		P1 - 7,500 lumens, 54W P2 - 10,000 lumens, 78W P3 - 12,000 lumens, 102W		MVOLT (120-277V) 347V 480V	-	-	-	-			
	 DSXF3 LED		P1 - 16,500 lumens, 111W P2 - 20,000 lumens, 138W P3 - 23,000 lumens, 165W P4 - 26,000 lumens, 189W			-	-	-	-			
RSXF LED Floodlighting	 RSXF1 LED		The RSX LED floodlighting luminaires are a complete solution for both renovation and new construction applications where value, an extensive range of options and industry-leading delivery are required.	P1 - 7,000 lumens, 51W P2 - 9,500 lumens, 72W P3 - 14,000 lumens, 109W P4 - 16,000 lumens, 133W	3000K / 70 CRI 4000K / 70 CRI 5000K / 70 CRI	MVOLT (120 – 277V)	High / Low Motion Sensor with Integral Photocell (using nLight AIR)	-	Yes	-		
	 RSXF2 LED			P1 - 10,000 lumens, 71W P2 - 16,000 lumens, 111W P3 - 20,000 lumens, 147W P4 - 24,000 lumens, 187W P5 - 25,000 lumens, 210W P6 - 29,000 lumens, 244W		HVOLT (347 – 480V) XVOLT (277 – 480V)						
	 RSXF3 LED			P1 - 26,000 lumens, 194W P2 - 30,000 lumens, 222W P3 - 34,000 lumens, 266W P4 - 39,000 lumens, 312W	3000K / 70 CRI 4000K / 70 CRI 5000K / 70 CRI	MVOLT (120 – 277V) HVOLT (347 – 480V) XVOLT (277 – 480V)					-	Yes
	 RSXF4 LED	P1 - 40,000 lumens, 275W P2 - 45,000 lumens, 320W P3 - 50,000 lumens, 369W P4 - 55,000 lumens, 431W P5 - 62,000 lumens, 483W P6 - 68,000 lumens, 546W P7 - 71,000 lumens, 520W P8 - 83,000 lumens, 646W		-		Yes					-	

FLOODLIGHTING

		Value Proposition in 30 Seconds	Lumen Packages	CCT & CRI	Voltage	Optional				
						Motion Sensor	Emergency Battery	nLIGHT AIR	CS	
HLF LED High Lumen Floodlighting	 HLF1 LED	<p>The HLF LED high lumen floodlights provide a lot of light where it is needed most. Capable of delivering over 100,000 lumens, the HLF is ideal for challenging lighting applications. In addition to flood optics, the HLF features hybrid silicone optics that create narrow distributions for spotlighting applications.</p>	P1 - 24,000 lumens, 163W	3000K / 70 CRI 4000K / 70 CRI 5000K / 70 CRI	MVOLT (120 – 277V) HVOLT (347 – 480V)	-	-	-	-	
			P2 - 29,000 lumens, 203W							
	P3 - 38,000 lumens, 289W									
	P4 - 43,000 lumens, 342W									
	P5 - 50,000 lumens, 368W									
	P6 - 102,000 lumens, 769W									
	 HLF2 LED									
TFX LED Floodlighting	 TFX1 LED	<p>The TFX LED family provides the best value for everyday floodlighting needs.</p>	7,300 lumens, 54W	4000K / 70 CRI 5000K / 70 CRI	MVOLT (120 – 277V) HVOLT (347 – 480V)	-	-	-	Yes	
	 TFX2 LED		13,200 lumens, 94W						Yes	
	 TFX3 LED		25,600 lumens 188W						Yes	
	 TFX4 LED		41,000 lumens, 296W							
			41,700 lumens, 286W							
 QTE LED	<p>The QTE LED floodlights are a long-lasting, energy-efficient solution for replacing quartz halogen floodlights.</p>	P1 - 2,500 lumens, 25W P2 - 4,400 lumens, 40W P3 - 6,900 lumens, 66W	4000K / 80 CRI 5000K / 80 CRI	120V	-	-	-	Yes		


Outdoor Lighting Quick Reference Guide

PARKING GARAGE, CANOPY & BOLLARD

		Value Proposition in 30 Seconds	Lumen Packages	CCT & CRI	Voltage	Optional			
						Motion Sensor	Emergency Battery	nLIGHT AIR	CS
VCPG LED Parking Garage	 VCPG	The VCPG LED brings visual comfort, energy efficiency and style to parking garage applications. The VCPGX provides the ultimate in visual comfort with a recessed lens and patented transition zone. Increase energy savings and gain code-compliance with the addition of nLight AIR controls.	P1 - 3,700 lumens, 27W	3000K / 80 CRI	MVOLT (120 – 277V) 347V 480V	High / Low Motion Sensor with Integral Photocell	8W / -20C 10W / 5C	Yes	-
			P2 - 4,700 lumens, 34W						
	P3 - 6,000 lumens, 43W		3500K / 80 CRI						
	P4 - 7,500 lumens, 56W		4000K / 80 CRI						
	P5 - 10,000 lumens, 82W		5000K / 80 CRI						
	P6 - 13,000 lumens, 108W		(70 CRI also available)						
	P7 - 16,000 lumens, 122W								
CNY LED	 CNY	The CNY LED provides the best value in canopy lighting	P0 - 3,500 lumens	4000K / 70 CRI	MVOLT (120 – 277V)	-	-	-	Yes
			P1 - 4,500 lumens	5000K / 70 CRI					
			P2 - 6,600 lumens						
RADEAN™	 RADEAN	The Radean LED bollard is the ideal companion to the Radean area luminaires for pedestrian spaces	P1 - 345 lumens	2700K / 70 CRI	MVOLT (120 – 277V) 347V	Yes	7W / 0C	-	-
			P2 - 644 lumens	3000K / 70 CRI					
			P3 - 1,036 lumens	3500K / 70 CRI					
			P4 - 1,460 lumens	4000K / 70 CRI					
			P5 - 2,314 lumens	5000K / 70 CRI					
D-Series LED	 DSXB	The D-Series LED bollard combines modern styling and durable construction making it ideal for public spaces.	350 - 1,600 lumens, 20W	3000K / 70 CRI	MVOLT (120 – 277V) 347V	-	23W / -20C	-	-
			530 - 2,250 lumens, 28W	4000K / 70 CRI					
			700 - 2,800 lumens, 39W	5000K / 70 CRI PC Amber LW Amber					
KBR8 LED	 KBR8	The KBR8 LED bollard's contemporary styling and energy efficiency makes it the right choice for replacing aging HID bollards.	350 - 900 lumens, 20W	3000K / 70 CRI	MVOLT (120 – 277V) 347V	-	23W / -20C	-	-
			530 - 1,250 lumens, 28W	4000K / 70 CRI					
			700 - 1,600 lumens, 39W	5000K / 70 CRI PC Amber LW Amber					

Outdoor Lighting Quick Reference Guide

SECURITY & RESIDENTIAL LIGHTING

						Optional			
		Value Proposition in 30 Seconds	Lumen Packages	CCT & CRI	Voltage	Motion Sensor	Emergency Battery	nLIGHT AIR	CS
BarnGuard LED	 BarnGuard (BGR)	The BarnGuard LED is an energy-efficient, long-lasting, cost-effective replacement for HID security fixtures.	P1 - 4,700 lumens, 36W	4000K / 70 CRI	MVOLT (120 – 277V)	-	-	-	Yes
			P2 - 7,900 lumens, 56W	5000K / 70 CRI					