



- PAD STAMPING:
1. PENN-UNION
 2. PB2-600N
 3. 2 AWG - 600 MCM
 4. AL9CU
 - 5.

NOTES:

1. MANUFACTURED FROM HIGH STRENGTH ALUMINUM ALLOY EXTRUSION
2. ELECTRO-TIN PLATED TO ENSURE MINIMUM CONTACT RESISTANCE AND CORROSION PROTECTION
3. CONNECTORS ARE RATED FOR 600V, 90°C APPLICATIONS
4. THE USE OF OXIDE INHIBITOR IS RECOMMENDED FOR ALL ALUMINUM TERMINATIONS
5. cULus LISTED PER UL486A-B FOR ALUMINUM AND COPPER CONDUCTORS AT 90°C
6. INSTALLATION TORQUE: 500 IN•LB
7. STRIP LENGTH: 1.38 UPPER HOLES, 2.56 LOWER HOLES
8. ALL DIMENSIONS IN INCHES UNLESS OTHERWISE SPECIFIED
9. APPROX. WEIGHT: 0.947 LB



| NO. | ECN | DATE |
|-----|-------|-----------|
| 3 | 11959 | 7/29/2020 |
| 2 | 11941 | 4/27/2020 |
| 1 | 11864 | 7/25/2019 |

| QTY. | PT. | NAME OR DESCRIPTION |
|--------------------------------------|-----|---------------------------------|
| 2 | 2 | SET SCREW, ALUMINUM, TIN PLATED |
| 1 | 1 | LUG BODY, ALUMINUM, TIN PLATED |
| ALUMINUM PANEL BOARD LUG | | |
| for 2 AWG - 600 MCM, 2 CONDUCTORS | | |
| REF. DWG'S: 5J10-96765 | | H:\5J10\96765_C |
| DRAWN BY: QB | | DATE: 6/1/2021 |
| SCALE: 1:1 | | INTERPRET PER ASME Y14.5-2009 |
| SIZE: B | | FILE: 5J10 |
| DWG. NO. PB2-600N | | REV. 3 |